

AWUS036NEH

802.11n/b/g Long-Rang USB Dongle

AWUS036NEH IEEE 802.11b/g/n Wireless USB adapter provides users to launch IEEE 802.11b/g/n wireless network at 150 Mbps in the 2.4GHz band, which is also compatible with IEEE 802.11b/g wireless devices at 54 Mbps. You can configure AWUS036NEH with ad-hoc mode to connect to other 2.4GHz wireless computers, or with Infrastructure mode to connect to a wireless AP or router for accessing to Internet.

AWUS036NEH includes a convenient Utility for scanning available networks and saving preferred networks that users usually connected with. Security encryption can also be configured by this utility.



Features

- Compatible with IEEE 802.11n, 802.11b/g/n wireless standards
- 2.4GHz frequency band, MIMO (Multiple Input Multiple Output)
- Complies with Universal Serial Bus Rev. 2.0 specifications
- High speed transfer TX data rate up to 150 Mbps
- Supports WPS by S/W
- Supports wireless data encryption with 64/128-bit WEP, WPA, WPA2, TKIP, AES
- Wide Range coverage
- Compliant with FCC Part 15.247 for US, ETS 300 328 for Europe
- Supports driver for Windows 2000, XP 32/64, Vista 32/64, Windows 7 Linux (2.4.x/2.6.x), Mac (10.4.x/10.5.x) Power PC& PC.

For further details:

Alfa Network Inc.,
4F-1 No. 106, Rueiguang Rd.,
Neihu District,
Taipei City, Taiwan.
<http://www.alfa.com.tw>
sales@alfa.com.tw
Tel:+886-2-27968477
Fax:+886-2-27968478

ALFA
NETWORK
Your Source of Hardware

AWUS036NEH

802.11n/b/g Long-Rang USB Dongle

Specification

Technical Specification	
standards	IEEE 802.11n draft 4.0 IEEE 802.11b/g USB v1.0/1.1/2.0
Data Rate	IEEE 802.11n 150Mbps IEEE 802.11a/g 54Mbps IEEE 802.11b 11Mbps
Output Power	IEEE 802.11g/n 22dBm @ 54Mbps 25dBm @ 6Mbps IEEE 802.11b @ 26dBm
Receiver Sensitivity	IEEE 802.11g/n -74dBm @ 54Mbps -71dBm @ MCS7, HT20 -66dBm @ MCS7, HT40 IEEE 802.11b -91dBm @ 11Mbps
Antenna	External RP-SMA 5dBi Dipole Antenna
Frequency Range	US, Canada 2.412GHz~2.462 GHz (CH1~CH11) EU 2.412GHz~2.472GHz (CH1~CH13) Japan 2.412GHz~2.484GHz (CH1~CH14)
Security	64/128-bit WEP Encryption, WPA, WPA2, TKIP, AES
Support OS	Windows XP/2000/Vista, Linux, Mac
Operating Voltage	DC 5V \pm 5%
Temperature	Operating: 0°C ~ +50°C Storage : -10°C ~ +65°C



For further details:

Alfa Network Inc.,
4F-1 No. 106, Rueiguang Rd.,
Neihu District,
Taipei City, Taiwan.
<http://www.alfa.com.tw>
sales@alfa.com.tw
Tel: +886-2-27968477
Fax: +886-2-27968478